











MULTI-AIR CONDITIONING SYSTEM



Features

- Super Powerful
 - Cools Faster than Conventional Models

Energy Saving



- Daikin Smart Refrigerant Control
- Daikin DC Inverter Compressor



- 3 Years Guarantee
- New Minimum & Maximum Fluctuation for Voltage Fluctuation
- Insect Resistant & Anti-Rust Coating

Convenience



- Remote Control via Smartphone (Daikin Mobile Controller)



Flap



Super Powerful



Odor Removal

Night Set Mode



Auto-Restart after



1111111 WIDE

Wide Angle

Louvers

ďΣ

Standby

Energy

Saving

Removable

Drain Pan

Power Failure



Comfort

Airflow

Mode

 $((\bullet))$

Daikin Mobile

Controller

(optional adaptor)

Programme

Dry Function

Self-Diagnosis with Remote Controller



Auto-Swing (Up & Down)



Enzyme Blue





Auto Fan Speed



Fcono

Mode

Mold-Proof

Air Filter

Quiet Operation



Indoor Unit

On / Off

Switch

Wipe-Clean

Flat Panel

On / Off Timer



*Protected up to 440V Can operate 130V - 264V



Multi S Specifications

Indoor Unit								
Model Name			CTKC25RVM	CTKC35RVM				
Power Supply			1 Phase / 220V / 60 Hz					
Front Panel Color		White						
Air Flow Rate	H /		11.0 (388)	11.5 (406)				
	M	m³/min	9.0 (318)	9.3 (328)				
	T /	cfm	6.6 (233)	6.7 (237)				
	SL	1/_	3.5 (124)					
Fan Speed			5 steps, Auto, Quiet					
Air Direction Control			Right, Left, Horizontal, Downwards					
Air Filter			Removable, Washable, Mildew Proof					
Sound Pressure Level	(H/M/L/SL)	dBA	38 / 33 / 25 / 22	39 / 34 / 26 / 22				
Dimension (H x W x D)		mm	285 x 770 x 223					
Net Weight		kg	9					
	Liquid	mm	Ф6.4					
Pipe Connection	Gas	mm	Ф9.5					
	Drain	mm	Ф16					
Heat Insulation	1	m	Both liquid and gas pipes					

	Out	door	Unit		
Model Name		MKC50RVM			
Power Supply		1 Phase / 220V / 60 Hz			
Max. Connectable Indo	or Unit	3			
Max. Connectable Indoo	r Unit Capacity	kW	8.5		
Color			White		
Compressor		Type	Hermetically Sealed Swing		
Refrigerant	<i>\delta</i>		R-32		
Sound Pressure Level (H/L)	dBA	49 / 44		
Dimension (H x W x D)	7	mm	550 x 675 x 284		
Net Weight		kg	37		
Operation Range		°CDB	10 - 46		
Piping Length		m	50 (total) / 25 (each room)		
Additional Refrigerant Amount			Chargeless		
Pipe Connection	Liquid	mm	Ф6.4 х 3		
	Gas	mm	Ф9.5 х 3		
Max Height		m	15 (indoor unit - outdoor unit) / 7.5 (between indoor units)		



Features

- 1. Single outdoor unit is connectable to up to five indoor units.
- 2. Compact and powerful system enables an outdoor unit to connect indoor units up to 205% of outdoor capacity.
- 3. Two wall-mounted type & duct-connected type indoor units are connectable.
- 4. Indoor units have a wide range of capacity classes from 2.5 to 7.1 kW.
- 5. All systems use next-generation R-32 refrigerant.
- 6. DC Inverter enables air conditioners to achieve high energy efficiency.



MIN!

Horizontal

Auto-Swing

Power Airflow Power Airflow **Dual Flans** Flan





Wide Angle Vertical Auto-Swing Louvers (Up & Down)





3D Airflow

Indoor Unit

On / Off

Switch

Intelligent

Eye

Outdoor Unit

Quiet Operation



Inverter Powerful Operation

Wireless Remote

Controller with

Backlight

Two-Area

Intelligent Eye

Night Quiet

Mode

Weekly

Timer



Model Name		MKM65PVM	MKM80PVM	MKM95PVM	MKM105PVM		
Power Supply		1 Phase / 220V / 60 Hz					
Number of Ports		4			5		
Max. Connected Indoor Units Capacity	kW	12.0 15.6					
Casing Color		Ivory White					
Compressor	Type	Hermetically Sealed Swing					
Refrigerant		R-32					
Sound Pressure Level (Rated)	dBA	48			53		
Dimension (H x W x D)	mm	695 x 930 x 350		990 x 940 x 320			
Net Weight	Kg	49		83			
Operation Range	°CDB	10 - 46					
Piping Length	m	60 (total)	70 (total)		80 (total)		
		30 (for each room)					
Additional Refrigerant Amount		Chargeless					
Max Height	m	15 (indoor unit - outdoor unit) / 7.5 (between indoor units)					

Note: Please see the Multi-Split Type Air Conditioners catalog for more info.



Econo Mode

Priority Room

Settina

Programme

Dry Function





Comfort

Airflow

Mode

யு

Home

Leave



Quiet Operation





Auto Fan



Enzyme Blue Wipe-Clean Deodorizing Filter Flat Panel



Night Set



Speed





24 Hour On / Off Timer



Self-Diagnosis with Remote Treatment of Outdoor Controller



Heat Exchange Fins

Note: The features vary in installed indoor units

DPH-MSF-202102B





DAIKIN AIRCONDITIONING PHILIPPINES INC.

Tel No.: (02) 5318 - 6800 | Customer Service: (02) 5318 - 6820

Branches:

ILOCOS Tel No.: (077) 600 - 2720 DAGUPAN Tel No.: (075) 615 - 2791 NAGA

Tel Fax: (054) 871 - 4177

||O||O**CEBU** CDO

Tel Fax: (033) 323 - 2340 Tel No.: (032) 348 - 0035 Tel Fax: (088) 868 - 6800 DAVAO Tel Fax: (082) 285 - 6008 **Authorized Dealer**

Auto-Restart after Power

Failure

• Specifications, designs, and other content appearing in this brochure are current as of February 2021 but subject to change without notice. • 1 year warranty for parts and labor | 5 years warranty for compressor only (Labor and Consumables are chargeable after

Daikin Philippines

